



City of Hermosa Beach

Public Works Department, 1315 Valley Drive, Hermosa Beach, CA 90254

PUBLIC RIGHT-OF-WAY PERMIT

PERMIT NO. PW11-0265

Status: VOID
 Issued: 08/03/2011
 Completed:
 Expires: 01/30/2012
 Issued By: HB

INSPECTION REQUIRED
 PHONE 310/318-0262 FOR INSPECTION APPOINTMENT.
 REQUESTS FOR INSPECTION MUST BE MADE NO LATER THAN NOON THE PRECEDING DAY INSPECTION.
 MONDAY INSPECTIONS MUST BE RECEIVED BY NOON THURSDAY.

The hard copy of this permit must be kept on the job site at all times to be shown to any authorized agent of the City upon request.

ADDRESS: 1315 VALLEY DR HB PARCEL: 4187-020-904 -
 LOCATION:
 DESCRIPTION: CURB & GUTTER, SIDEWALK, DRIVEWAY

OWNER: HERMOSA BEACH CITY PHONE:
 ADDRESS: 00000, ,

CONTRACTOR: PHONE:
 ADDRESS: , ,
 CITY LICENSE #: STATE LIC. #:

A. STREET EXCAVATION PERMIT	B. MISCELLANEOUS USE PERMIT	C. ENCROACHMENT PERMIT
Curb & Gutter Y	Street/Lane Closure N	Fence N
Sidewalk Y	Material Storage/Drop-Off N	Street Tree N
Driveway Y	Crane N	Planter N
Sewer N	Temporary Fence N	D. Other:
Water N	Scaffolding N	
Utility Service Connection N	Staging N	
Street Pavement N	Roll-Off Bin N	
	Parking Meter N	
Permit valid for 180 days from issuance.	Permit valid for 14 days from issuance.	Permit valid for 180 days from issuance.

INSURANCE: On File: Y Not Required: N

Deposit to be refunded to PAYOR:
 Bond deposit refund request to Finance on: by:

FEE DESCRIPTION	TRAN. CODE	AMOUNT	INSPECTIONS		
			COMMENTS	DATE	BY
Work Guarantee Deposit	5015	\$0.00			
Parking Meter Fee	5020	\$0.00			
Street Excavation Fee	5090	\$340.00			
Sewer Lateral Fee	5095	\$0.00			
Utility Fee	5090	\$0.00			
Sewer Cap Fee	5085	\$0.00			
Miscellaneous Fee	5070	\$0.00			
TOTAL		\$340.00			
			FINAL ACCEPTANCE AND RELEASE		

PROTECT OUR OCEAN QUALITY

Best Management Practices are required to protect water quality. No construction debris and/or pollutants are to leave the site and enter the storm drain system. This includes sediment, trash, oil, grease, concrete saw-cutting slurry, wash water from painting, stucco or concrete clean up. Violations are subject to fines and/or work stoppage (Municipal Code Sections 8.44 & 1..12.010).

Validation of this permit **SHALL NOT** be held to permit or to be an approval of the violation of any applicable provisions of the Hermosa Beach City Code and the City is held harmless from the action or accidents caused by the permittee, his employees or equipment in the performance of the work described or covered in this permit.

I hereby acknowledge that I have read this application (front and back) and that the information given is correct. I agree to comply with all applicable City Ordinances, State Laws and the requirements of this permit.

 Signature of Contractor / Authorized Agent Signature of Owner (If Owner / Builder)

SEE REVERSE FOR STANDARD REQUIREMENTS

STANDARD REQUIREMENTS

1. **NOTIFICATION REQUIREMENT:** The contractor shall notify the adjacent property owners and all affected residents of any work that will impact them. This includes all street or lane closures and any work that will generate extreme noise (i.e., demolition).
2. **WORKING HOURS:** Permitted construction is allowed to take place only between the hours of 8:00 a.m. and 7:00 p.m., Monday through Friday, and 9:00 a.m. to 5:00 p.m. on Saturdays. Permitted construction is prohibited on Sundays and national holidays.
3. All construction, unless otherwise specified, shall be done in accordance with the current edition of "Standard Specifications for Public Works Construction" and the "Highway Permit Ordinance Division 1 of Title 16."
4. Traffic may be restricted only between the hours of 9:00 a.m. to 3:00 p.m. and subject to review by the Director of Public Works. Excavations shall be backfilled or plated to maintain existing traffic lanes other than during these hours.
5. One lane of traffic in each direction shall be maintained at all times on all major and secondary highways.
6. Traffic controls throughout permitted construction shall conform to the current Edition of "Work Area Traffic Control Handbook" (WATCH); permittee shall provide and maintain all such signs, lights and devices.
7. Pedestrian walkway must be maintained with safety fencing or barrier separation from adjacent excavation when left unattended.
8. Permanent pavement repairs shall be made within thirty (30) days but no less than two weeks after excavation work is completed. Inspector's approval is required before permanent repairs are made.
9. Utility mainline projects are required to slurry seal the full street width where excavation is made in street less than five (5) years old. Permittee is responsible for replacing all traffic striping and pavement markings.
10. **BACKFILL:** The material used for backfill shall have a sand equivalent of not less than 30% as determined by tests from a qualified soils laboratory. Material encountered in excavation that will meet this requirement may be used for backfill. If excavated materials fail to meet this requirement the contractor shall use sand or crushed aggregate as backfill. If cement slurry used, no compaction tests will be required. Compaction shall be done by mechanical means. Jetting is not allowed. The maximum lift shall be 0.67' when handheld compaction equipment is used. Free falling weight compaction equipment shall not be allowed. Relative compaction required shall be 90% except for the final 0.5', which shall be 95%. Costs of the compaction test are to be borne by the permittee. The frequency of such testing will be determined by the inspector and will be sufficient to ensure that requirements have been met. Determination of frequency will be based on variables such as the nature of the material or the efficiency of the contractor's methods.
11. All graffiti must be removed within 24 hours of notification.
12. Where excavation tunnels under curb and gutter or sidewalk, or other improvements, which are to remain in place, or crosses an intersection, backfill shall be cement slurry consisting of one (1) sack of cement per cubic yard of slurry. The slurry shall be placed in a method satisfactory to the inspector to assure the elimination of any cavities.
13. Call Underground Service Alert (U.S.A.) at least forty-eight (48) hours prior to start of work: 1-800-227-2600.
14. All changes in the Scope of Work must have prior approval by the City Engineer.
15. Any excavation of five (5') feet or more in depth will require a permit from the Division of Industrial Safety (DIS) prior to obtaining a City Permit.
16. All Survey Monuments destroyed as a result of the contractor's work shall be reset "in kind" at the contractor's expense by a licensed Surveyor and recorded with the County Recorder's Office. Copies of all ties to reset monuments will be supplied to the City prior to release of work guarantee deposit.
17. Sandbags and/or other stormwater BMPs shall be installed and maintained for erosion control during October 15th through April 15th and may be required at other times.
18. All pavement trenches are to be repaired per "City of Hermosa Beach Standard Drawing No. 117, Trench Backfill and Pavement Repair."
18. All work done within the public right-of-way shall be done by a licensed contractor possessing a Class A, C-12 or C-34 License for all trenching and paving, a Class C-08 License for all concrete work, and a Class B License for minor curb, gutter and sidewalk.
19. Applicant shall maintain and keep in force at all times during construction a policy of liability insurance naming the City as additionally insured in the amount of one million dollars (\$1,000,000) minimum.
20. A work guarantee deposit is required for all work done within the public right-of-way. The amount of said deposit will be determined by the Public Works Department (minimum deposit is set at \$1,600). Once all improvements are in place and approved, the cash deposit will be refunded. If trenching and resurfacing in street area, deposit will be held for one year.
21. **SEWER LATERAL:** When installing a new sewer lateral, existing lateral must be plugged at the main and abandoned lateral shall be filled with cement slurry to the property line.